



© 2014 Mazda Motor of America, Inc.

<b>Subject:</b>  <b>SPEEDOMETER REPLACEMENT PROCEDURE</b>	<b>Bulletin No:</b> 09-034/14
	<b>Last Issued:</b> 08/15/2014

## BULLETIN NOTE

- This bulletin supersedes the previous servious bulletins AD-003/97 issued 02/25/97 and 09-026/04 issued on 07/01/04. The APPLICABLE MODEL(S)/VINS has been revised.
- Changes are noted below beside the change bar in Red.

## APPLICABLE MODEL(S)/VINS

1990-1994 323	1992-1995 929	2006-2015 Mazda5
1992-1995 MX-3	1995-2002 Millenia	2003-2015 Mazda6
1990-2003 Protege	1991-1994 Navajo	2013-2015 Mazda CX-5
2002-2003 Protege5	1990-2006 MPV	2007-2012 Mazda CX-7
1990-2005 Miata	1995-2009 B-Series	2007-2015 Mazda CX-9
1993-1995 RX-7	2001-2011 Tribute	2006-2015 Mazda MX-5
1990-1995 MX-6	2011-2014 Mazda2	2004-2011 Mazda RX-8
1990-2002 626	2004-2015 Mazda3	

## DESCRIPTION

In accordance with Federal regulations, follow the procedure listed below when replacing a speedometer.

### NOTE:

- Mazda vehicles are manufactured with tamper-proof speedometers.
- When a speedometer is replaced, the new speedometer will read zero (0) miles.
- This procedure is extremely important to accurately represent actual vehicle mileage.
- Prior to speedometer removal, complete the information required on the "Speedometer Replacement Label".
- Labels can only be ordered through MStore, not MDCS.

**CONSUMER NOTICE:** The information and instructions in this bulletin are intended for use by skilled technicians. Mazda technicians utilize the proper tools/equipment and take training to correctly and safely maintain Mazda vehicles. These instructions should not be performed by "do-it-yourselfers." Customers should not assume this bulletin applies to their vehicle or that their vehicle will develop the described concern. To determine if the information applies, customers should contact their nearest authorized Mazda dealership. Mazda North American Operations reserves the right to alter the specifications and contents of this bulletin without obligation or advance notice. All rights reserved. No part of this bulletin may be reproduced in any form or by any means, electronic or mechanical---including photocopying and recording and the use of any kind of information storage and retrieval system ---without permission in writing.

## REPAIR PROCEDURE

### SPEEDOMETER REPLACEMENT

1. Order "Speedometer Replacement Labels" through MStore.
2. Record vehicle mileage before removing the speedometer.
3. Remove and replace the speedometer according to the appropriate workshop manual.
4. Complete the following information on the "Speedometer Replacement Label."
  - a. Mileage (before speedometer replacement).
  - b. Date of replacement.
  - c. Dealer code.

<p><b>SPEEDOMETER REPLACEMENT</b> Mileage: _____ (Before Replacement) Date Replaced: ____/____/____ Dealer Code: _____</p>
--

1284a

Complete Information and Install  
On Driver's Side "B" Pillar

5. Attach the completed label to the driver's side "B" pillar.

### PART(S) INFORMATION

Part Number	Description	Qty.	Notes
9999-95-SPDO-97	Speedometer Replacement Labels	1 (Sheet)	Order labels through MStore only. Each sheet contains 20 labels.